

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Claims 1-13. (Canceled).

14. (Currently Amended) A method of embedding identification information in a main body of data of a digital record medium by using an error correction technology comprising;

error correction encoding to digital data including digital contents to correct the error occurring in the transmission line with which the main body of data is obtained;

embedding the identification information to a part of said main body of data to which an error correction encoding has been [[is]] performed based on position information;

embedding the position information after embedding the identification information to a part of said main body of data to which an error correction encoding has been [[is]] performed; and

storing said main body of data including [[said]] the embedded identification information and the embedded position information into said digital record medium.

15. (Previously Presented) The method according to claim 14, wherein said identification information is embedded to a data part stored in an area where control information of contents data in a record area is recorded.

16. (Canceled).

17. (Previously Presented) The method according to claim 14, wherein said identification information has a plurality of partial identification information; an information to acquire the embedded position of said identification information has an initial value information, an embedded position information indicating an embedded position of said plurality of partial identification information, and a plurality of position information to acquire a position of said embedded position information;

a first position information to acquire the position of said embedded position information is recorded at a position obtained by converting said initial value information by a predetermined function or a position shown by a position obtained as a result of the conversion; and

a second or later position information is recorded in another position of the position obtained by converting a storage information of a position of a result when an information stored at another position of a side where said position information is not stored is further converted by said predetermined function in any positions obtained by a conversion result of said predetermined function, or a storage information at a position indicated to a position of a result of conversion one by one.

18. (Previously Presented) The method according to claim 14, wherein said identification information has a plurality of partial identification information;

an information to acquire an embedded position of said identification information has an initial value information, an embedded position information indicating the embedded position of said plurality of partial identification information, and a plurality of position information to acquire a position of said embedded position information;

an initial position information is recorded at a position obtained by converting said initial value information by a predetermined function or a position shown by a position obtained as a result of conversion by said predetermined conversion formula; and

a position information after that is recorded at a position based on a data recorded by a predetermined distance at a position indicated by a position information obtained immediately before or a distance obtained by a predetermined conversion formula, or a position obtained by converting a position information obtained immediately before by a predetermined conversion formula.

19. (Previously Presented) The method according to claim 14, wherein an embedded position of said identification information is given by a table form.

20. (Previously Presented) The method according to claim 14, wherein said presentation target data is scrambled or encoded to make said identification information a key before an error correction encoding is performed.

21. (Currently Amended) A method of extracting an identification information from a main body of data of a digital record medium in which includes embedded

identification information and position information by using an error correction technology comprising;

reading said main body of data in which includes embedded identification information from said digital record medium;

extracting said identification information from the main body by an error correction decoding based on the position information; and

error correction decoding the main body of data after extracting said identification information in which original digital data is obtained.

22. (Currently Amended) A method of embedding identification information in a main body of data of a digital record medium by using an error correction technology comprising;

encrypting digital data including digital contents by using said identification information;

error correction encoding to said encrypted digital data including digital contents to correct the error occurring in the transmission line with which the main body of data is obtained;

embedding the identification information to a part of said main body of data to which an error correction encoding is performed based on position information;

embedding the position information to a [[to a]] part of said main body of data to which an error correction encoding is performed; and

storing said main body of data including said embedded identification information into said digital record medium.

23. (Previously Presented) The record medium according to claim 22, wherein said identification information is embedded to a data part stored in an area where control information of contents data in a record area is recorded.